HYUNDAI

Display Solutions by Expertise.

GLOBAL HEADQUARTERS

HYUNDAI IT CORP.
San 136-1, Ami-ri, Bubal-eub
Ichon-si, Kyungki-do, 467-701,
The Republic of Korea
Phone: +82 31 639 8560
Fax: +82 31 636 4231
E-mail: uno@hyundaiit.com

EUROPEAN HEADQUARTERS

HYUNDAI IT EUROPE GmbH
Geheimrat-Hummel-Platz 2
65239 Hochheim
Germany
Phone: +49 6146-904-0
Fax. +49 6146-904-110
E-mail: info@hyundaiit.eu

FRANCE
Phone: +33 155472660
E-mail: france@hyundaiit.eu

GERMANY
Phone: +49 6146-904-0
E-mail: germany@hyundaiit.eu

POLAND
Phone: +48 605414565
E-mail: poland@hyundaiit.eu

SCANDINAVIA
Phone: +46 133292927
E-mail: scandinavia@hyundaiit.eu

SPAIN
Phone: +34 638841976
E-mail: spain@hyundaiit.eu

UNITED KINGDOM
Phone: +49 6146-904-0
E-mail: uk@hyundaiit.eu

www.hyundaiit.com

Professional Display Solutions 2010



Display Solutions by Expertise.

HYUNDAI

Display Solutions by Expertise

Since the mid-90s, the name HYUNDAI has been synonymous with the design and production of state-of-the-art display technologies. Advanced devices offering sophisticated design and supreme image quality – with "built-in" future-proofing.

On the one hand the ongoing process of digitalization leads continuously to new fields of operation for digital displays. On the other hand the technical progress enables new capabilities in development and production. Being an expert for display solutions HYUNDAI IT brings both together: new requirements from market and the advantages of enhanced production techniques. As a result there are innovative display solutions which will revolutionize the display market with state-of-the-art technology, new functions and designs.

Join us on a voyage of discovery and explore today what display solutions will be like tomorrow. HYUNDAI IT: The name of choice for a broad range of future-oriented applications. The technology of tomorrow, for today's trend and quality conscious customers. Welcome to the future. Welcome to HYUNDAI IT.

Indoor & Outdoor Digital Signage

More and more large-sized digital LCD screens are replacing existing analogue display media for the presentation of information and advertising messages. Combined with a professional "Content Management Software" and attractively created content these "Digital Signage Systems" are launching to the next generation of public display devices. By using special "Out-Of-Home" LCD panels HYUNDAI IT's indoor and outdoor public displays ensure the presentation of digital signage contents in a pin sharp, high bright and brilliant picture quality. Meeting all necessary technical requirements for professional display equipment these enhanced displays ensure a reliable and failure-free operation in any kind of indoor or outdoor environment. Providing an integrated video wall function as well as the options for touch screen functionality and tempered glass surface the HYUNDAI IT Digital Signage Displays are the most flexible and versatile visual interface for all kind of digital signage solution.

Touch Screen Monitors

HYUNDAI IT touch screen monitors combine the conventional output function with a touch controlled input function. This bi-directional interface makes the screens the easiest solution for interactive information flow and controlling of systems. Due to their solid design the monitors are resistant to moisture and dust and thus ensuring a long lifetime even if they are used for applications with a high operational demand, like public information kiosk systems.

3D Displays

Opening access to another dimension HYUNDAI IT's 3D displays provide a new experience in virtual reality. In combination with professional computer aided engineering software, 3D models can be presented more plastically and thus closer to reality. Also for the post production of 3D movies and pictures as well as for PC gaming the new 3D monitors will be the first choice. Beside 3D operations the displays can be used as conventional monitor dealing with 2D contents without restrictions.

Outdoor Digital Signage

Enhanced Outdoor Displays for Digital Signage

The market for outdoor digital signage is growing worldwide. Providing different advantages compared to conventional outdoor advertising media, digital signage will be an interesting media for advertisers, outdoor media companies, cities and universities in the near future. Its high flexibility and the possibility of just-in-time content changes makes digital signage the perfect media for reaching target groups in a society which becomes more and more mobile.

HYUNDAI IT's outdoor displays represent state-of-the-art display technology for any outdoor environment. Meeting the highest industrial standards, they provide a high degree of operational reliability and superior image quality, which are important preconditions for attracting the attention of today's audience.

All-Weather Capable

Fitted with an intelligent cooling and heating system, the outdoor displays are well prepared for standing any weather conditions from -40°C to +50°C.

IP 55/65 Confirmity

In order to protect the display against outside influences the outdoor displays meet the requirements of IP55 as basic and those of IP65 optionally.

Air-Looping-System

In order to protect the LCD panel against so called blackouts (black areas on the screen in the wake of overheating), the outdoor displays are equipped with a smart air-looping-system.

Transflective Panel NEW

A transflective panel uses the sunlight to increase the display's brightness. In combination with the regular backlight the sunlight reflector makes it possible to reach a brightness of 3000 cd/m² in case of sunlight ambience is 80K lux.

LED Backlight

Compared to a CCFL backlight, a LED backlight enables a high brightness of 2500 cd/m². Reducing the power consumption the LED backlight makes the display an environmental friendly product.

Sunlight-Ready

A special anti-reflection treatment reduces reflections on the display's surface. Additionally the panel is protected by an UV filter coating.

Auto Brightness Control

An integrated light sensor that measures the ambient light takes care that the panel's brightness will be adjusted to the ambient lightning conditions. As a result the power consumption will be reduced while the panel's lifetime will be increased.

Anti-Vandal Protection

Thanks to a special tempered security glass HYUNDAI IT's outdoor displays are well protected against any vandalism attacks.

Anti-Graffiti Protection

A special coating on the display allows an easy removal of colours without any damage of the display's surface.

NEW

Mode Name			H460SC	H460SL	H466ST	H705SL
Display Panel	Screen Size		116,84 cm | 46"	116,84 cm | 46"	116,84 cm | 46"	177,8 cm | 70"
	Panel Type		S-PVA	S-PVA	S-PVA	S-PVA
	Transflective		No	No	Yes	no
	Active Display Area (mm)		1018.35 x 572.54	1018.35 x 572.54	1018.35 x 572.54	1549.44 x 871.56
	Number of Pixels		1366 x 768 (WUXGA)	1366 x 768 (WUXGA)	1366 x 768 (WUXGA)	1920 x 1080 (WUXGA)
	Aspect Ratio		16 : 9	16 : 9	16 : 9	16 : 9
	Display Colors		16.7 Mil	16.7 Mil	16.7 Mil	16.7 Mil
	Brightness (cd/m²)/(typ)		1500	2500	2400 - 3000	2000
	Contrast Ratio		3000 : 1	4.000 : 1 | 1.000 000 : 1 (DCR)	2900 : 1	2500 : 1
	Response Time (ms, GTG)		8	8	8	8
	Viewing Angle (H°/V°)		178°/178°	178°/178°	178°/178°	178°/178°
	Life Time		50,000h	30,000h	30,000h	30,000h
	Backlight type		CCFL	LED	CCFL	LED
Connectivity & Control	Input	VGA (15pin D-Sub)	1	1	1	1
		HDMI	1	1	1	1
	Power Requirement	Operating Voltage	100 – 240VAC	100 – 240VAC	100 – 240VAC	100 – 240VAC
		Consumption (typ) (W)	450 (Operating heating: Max. 1,2 KW)	500 (Operating heating: Max. 1,2 KW)	450 (Operating heating: Max. 1,2 KW)	1.2KW (Operating heating cooling system: Max.3.5KW)
	Auto Cooling System		Yes	Yes	Yes	Yes
	Auto Heating System		Yes	Yes	Yes	Yes
Features	Anti-Vandal Glass		Yes	Yes	Yes	Yes
	Auto Brightness Sensor		Yes	Yes	Yes	Yes
	Anti-Grafiti Coating		option	option	option	option
	Touch Screen		No (option: model H460SLI)	No (option: model H460SLI)	No (option: model H460STI)	No (option: model H705SLI)
Mechanical	Dimension	Set (W x H x L mm)	700 x 1950 x 245	700 x 1950 x 245	700 x 1950 x 245	1051 x 2200 x 305
	Weight (kg)	Set (Weight kg)	125	125	125	125
	Surface	treatment	Powder coated, Powder salty option	Powder coated, Powder salty option	Powder coated, Powder salty option	Powder coated, Powder salty option
Environmental conditions	Temperature operational (°C)		-40/50 (min/max)	-40/50 (min/max)	-40/50 (min/max)	-40/50 (min/max)
	Temperature storage (°C)		-20/60 (min/max)	-20/60 (min/max)	-20/60 (min/max)	-20/60 (min/max)
	Humidity (non-condensing) (%)		10 – 80	10 – 80	10 – 80	10 – 80
Approvals	EMI/EMC | Safety		FCC, CE | cTUVus, TUV, CB	FCC, CE | cTUVus, TUV, CB	FCC, CE | cTUVus, TUV, CB	FCC, CE | cTUVus, TUV, CB
	Ingress Protection		IP55 – IP65	IP55 – IP65	IP55 – IP65	IP55 – IP65

Technical details are subject of changes without further notice. Errors expected.

HYUNDAI

Outdoor Digital Signage

Key Features/Benefits

- Delivers high quality video on wide format
- Sunlight proof display technology
- Integrated stereo audio speakers
- Auto Brightness Sensor
- Compliant with IP65
- Anti-Vandal bonding glass (option)
- Auto Cooling & Heating System
- Wireless streaming thru transmitter unit
- Optical Bonding Glass
- Scalable system design for later expansion
- Compatibility with common fuel dispensers





Gas Station Digital Signage

HYUNDAI IT's gas station digital signage has been developed to bring media contents, like advertisings, promotional spots or weather, news and traffic information to motorists while they refill their fuel. It is designed to be placed on common fuel dispenser tabletops at gas stations. Being equipped with a sunlight-proof and optical bonding glass and an automatic cooling and heating system, it is ready to operate in a wide range of environmental conditions. Providing the opportunity to work with a wireless connection, the system can be easily implemented in existing infrastructures without high installation costs.

Model Name			H2010	T2010
Display Panel		Screen Size	50.1 cm | 20.1"	—
		Screen Q'ty	2 (Dual)	—
		Active Display Area (mm)	408 (H) x 306 (V)	—
		Number of Pixels	640 x R.G.B x 480	—
		Aspect Ratio	4 : 3	—
		Display Colors	0.26 Mil.	—
		Brightness (cd/m²) / (typical)	600 (200~1000)	—
		Contrast Ratio	600 : 1	—
		Response Time (ms) / (typ)	Tr : 3ms/Tf : 5ms	—
		Viewing Angle	80°(L) / 80°(R) / 70°(U) / 60°(D)	—
		Back light system	84 LED x 2	—
Glass		Glass Treatment	AR Coating	—
		Glass Thick (mm)	5	—
Resolution (Max)		In/Output	640 x 480 (31.5 kHz / 59.9Hz)	
Port	Input	HDMI	—	1
		PC Audio	—	1
		Intranet	—	1 (ETH0)
		LAN	—	1(ETH1)
		RS232C	—	1 (Updata)
	In / Output	RF ANT	2	2
Power		Input Voltage	100 ~ 240VAC	100 ~ 240VAC
		Consumption On / Working (typ) (w)	85	11
		AC ON/OFF S/W	1 (Internal)	1 (External)
Cooling System		Fan	1	1
		Fan Speed (rpm) (typ)	2600	—
Speaker		Output	10W x 2	—
RF Ant		Gain	2.4GHz : 3dBi / 5.75GHz : 5dBi	
Wireless		Standard Conformance	IEEE 802.11a, 802.11b, 802.11g	
		Antenna	Two U.FL antenna connectors for diversity function	
Mechanical	Dimension	Set (W x H x L) (mm)	547.7 x 453.8 x 317.2	390 x 45 x 210
	Weight	Set Weight (kg)	28.5kg	2.8kg
	Accessories		Installation Manual, Power Cable, RF Ant*2, Ant Bracket (Option)	Power cord, RF Ant*2, RF Cable*2, Ant Bracket (Option)
Safety & Regulations		Standard	UL/CSA, FCC, NEMA 4	UL/CSA, FCC
		RoHS, WEEE	yes	yes

Technical details are subject of changes without further notice. Errors expected.

Wireless Communication



Indoor Digital Signage | Metal Frame

Fields of Operation

According to the sophisticated product design, the HYUNDAI IT Public Displays meet all necessary preconditions to be used for the different kind of digital signage systems, such as:

- Information: e.g. traffic information at the airport
- Advertising: e.g. in-store promotion in retail establishments
- Sales support: e.g. last minute offers in travel agencies
- Brand building: e.g. brand communication during exhibitions & events
- Convenience: e.g. digital signage in restaurant waiting areas
- Presentation: e.g. conferencing & meeting environments

Special Out-Of-Home LCD Panel

By using commercial grade LCD panels for Out-Of-Home applications the HYUNDAI IT Digital Signage Displays have a higher brightness and contrast than standard LCD TV panels. Our LCD panels enable permanent operation with delivering clear and bright image contents. They can be used in portrait or landscape orientation without any losses of quality.

High Brightness & Contrast

Achieving a brightness from 450 to 1500 cd/m² and working with a smart dynamic contrast technology, the special Out-Of-Home panels ensure bright and sharp pictures with a facsimile depth, even in bright enlightened environments.

Regular LCD TV Panel

HYUNDAI IT Out-Of-Home Panel

Metal Frame Housing

As most of the HYUNDAI Digital Signage Displays have a solid metal frame housing it is guaranteed that the panel is well protected especially for public area installations. In addition, the metal frame gives the product a high quality and an appealingly optical appearance.

Full-HD Resolution

Having a resolution of either 1366 x 768 or 1920 x 1080, HYUNDAI IT Digital Signage can display high-resolution and more data information on the LCD screen by an aspect ratio of 16:9. The Full-HD resolution ensures brighter and sharper images if HD graphics and videos can display.

Full HD

HD ready

Wide Viewing Angle

The wider the panel's viewing angle is the more viewers are able to see the contents in a high quality. That matters for both meeting environments as well as public area installations. Coping with a wide viewing angle of 178° (h/v) HYUNDAI IT Digital Signage bring the content to the entire audience.

178° Wide View Angle

Fast Response Time

A fast response time of 8ms ensures the displaying of a clear image quality without ghosting effects for any fast moving video or image content.

High Connectivity

Providing an array of various professional input and output connectors [HDMI, DVI, Component/Composite (BNC), VGA] HYUNDAI IT Digital Signage afford an easy, flexible and multiple connection to a broad range of external A/V devices.

Heat Control & Cooling System

In order to avoid any image corruption or downtime by overheating HYUNDAI IT Digital Signage Displays are equipped with an innovative built-in fan & heat control system, which makes the displays ready for the operation in any climatic environment.

Remote Control (RS232C)

For an easy set-up and maintenance the built-in RS-232C port allows the remote controlling and configuration of the display's functions.

Wall Mounting

Wall mounting holes according to the VESA standard (Flat Panel Mounting Interface Standard) ensure the compatibility and thus an easy installation with universal wall-mounting brackets.

Environment-Friendly

Being compliant with the European RoHS directive and working with low power consumption during operation and power saving mode (< 1W) the displays conserve resources and operate environment-friendly.

RoHS COMPLIANT 2002/95/EC

Built-In Video Wall Function

Due to the built-in multi display wall function the HYUNDAI IT Public Displays are well prepared for installing video wall configurations including up to 5 by 5 single units. For this reason no additional expensive equipment like video split processors is necessary.

Samples of Multi Display Wall Configurations

Daisy Chain Connection

In order to realize a multi display wall, the single units are linked by a Daisy Chain connection over HDMI, Component or the D-Sub interface. This implicates that just one display (master unit) needs a direct connection to the video source. The configuration of each display, regarding its individual ID and position in the matrix, can be easily set-up using the on-screen menu or the RS232C interface. The built-in video wall function allows flexible configuration and easy installation.



Ultra Narrow Bezel Design NEW

Coming with an ultra narrow bezel design, HYUNDAI IT Digital Signage Displays are dedicated to build video walls. Combined with the cutting edge function – which allows displaying the full picture content – the smart design of the HYUNDAI public displays ensures a maximum screen area with a minimum of viewable interruptions.



Multi Touch Screen Function (Option)

As an option all HYUNDAI IT Digital Signage Displays can be equipped with touch screen functionality. Based on the infrared ray matrix technology it's possible to operate the displays in either single- or multi-touch mode. That makes the HYUNDAI IT Digital Signage Displays a smart touch screen solution for interactive applications.

Type	Infrared (Matrix)
Application	Graphics Intensive, Severe Duty, Mission Critical Applications
Light Transmission	92~100%
Response Time	16ms
Touch Accuracy	98.5~99%
Environment	Indoor/Outdoor
Operating Temp	-41°C ~ +70°C
Life	Tested to perform over 100 million touches on a single point
Surface Hardness	5mm with Anti-Vandal
Input Mode	Bare or gloved finger, stylus, pen etc., any object that blocks light
Function	Senses interruption of invisible infrared array. Fully ADA compliant.
Size	24" ~ 57"
Usage	Large Screen, DID

Technical details are subject of changes without further notice. Errors expected.

Motion Sensor (Option) NEW

For installation sites where contents only need to be displayed on demand (e.g. information terminals), a display with an integrated motion sensor offers a smart solution. Using a passive infrared sensor (PIR), the display starts showing contents when human motion is detected within the sensor's detection area. After an adjustable delay time (5 sec. to 18 min.) the display automatically turns to stand-by mode in case of no viewers in front. This operation on demand reduces power consumption and extends the panel's life time.

Tempered Security Glass (Option)

In order to protect the displays against vandal attacks and thus avoiding additional costs during the operational period it is possible to cover the screens with a tempered security glass. Combined with the opportunity of locking the keys for the on-screen menu and the solid metal frame housing the HYUNDAI IT Digital Signage Displays are the perfect visual equipment for the usage in high frequented public areas.

Optical Bonding Displays

For installations in environments with brightest lightning conditions – even bright sunlight – HYUNDAI IT provides special displays which are based on the optical bonding technique. This leads to the advantage that glare and reflection on the screens are reduced to a minimum while brightness is increased at the same time.

Due to a special coating the screens are protected against UV radiation, too. A digital signage screen behind a shop window which is regarded from the outdoor area is a typical application field for this special solution.

Advantages of optical Bonding

- Increases outdoor visibility (sunlight readability) as much as 400%
- Ensures a 99% penetration rate
- Improves contrast ratio
- 300% increased protection against shocks and scratches
- Prevents glass fogging
- Excellent resistance to temperature changes and dust

Regular Optical Bonding



Transflective Displays

The transflective displays technology contains a combination of both the conventional backlight transmissive mode as well as reflective mode characteristics. Depending on the ambient light conditions the advantage of either one or the other mode guarantees the readability of the screen contents at any time. By using the rear reflector, sunlight reflections increase the display's brightness. In case of darker ambient light conditions the backlight ensures the required display brightness. By the use of the ambient light for increasing the brightness, the power consumption of the backlight will be reduced and less heat is generated. This leads to a longer lifetime of the display.



All-In-One Displays

HYUNDAI IT's all-in-one displays are combining public display and built-in player functionality. Being equipped with a built-in PC, a network player or a multimedia player (MMP), these all-in-one displays enable easy installations without any additional AV equipment.



Wide View Displays

Wide view displays are characterized by their special aspect ratio whose height is less than half of its width. This brings the benefit that the wide view displays will fit into places where displays with a regular height can not be installed. For example metros and trams or space between door and ceiling are locations where wide view displays can be used as signage or advertising medium.

Metal Frame Displays

Model		D220ML	D320ML	D405ML	D407ML	D425ML	D466ML
		NEW					NEW
Panel	Screen Size (diagonal)	54,6 cm | 21,5"	81,3 cm | 32"	101,6 cm | 40"	101,6 | 40"	106,7 cm | 42"	116,8 cm | 46"
	Panel type	S-PVA	S-PVA	S-PVA	S-PVA	IPS	S-PVA
	Active Display Area (mm)	476.64 x 268.11	697.68 x 392.25	885.6 x 498.15	885.6 x 498.15	930.3 x 523.0	1018.35 x 572.54
	Resolution	1920 x 1080	1366 x 768	1920 x 1080	1920 x 1080	1920 x 1080	1366 x 768
	Aspect Ratio	16:9	16:9	16:9	16:9	16:9	16:9
	Display Colors	16.7 M	16.7 M	16.7 M	16.7 M	16.7 M	16.7 M
	Brightness (Typ)	300 cd/m²	450 cd/m²	450 cd/m²	700 cd/m²	500 cd/m²	1500 cd/m²
	Contrast Ratio	1000:1	4000:1	4000:1	3000:1	800:1	2000:1
	Response Time	8 ms	8 ms	8 ms	8 ms	9 ms	8 ms
	Viewing Angle	170°/160°	178°/178°	178°/178°	178°/178°	178°/178°	178°/178°
	Lifetime	50,000h	50,000h	50,000h	50,000h	50,000h	50,000h
Resolution	Monitor (Frequency H/V)	1360 x 768 (49,02kHz/60Hz)	1360 x 768 (49,02kHz/60Hz)	1920 x 1080 (67,5kHz/60Hz)	1920 x 1080 (67,5kHz/60Hz)	1920 x 1080 (67,5kHz/60Hz)	1360 x 768 (49,02k Hz/60Hz)
	DTV	1080p (Multi Screen: 1080p)	1080i (Multi Screen: 720p)	1080p (Multi Screen: 1080p)	1080p (Multi Screen: 1080p)	1080p (Multi Screen: 1080p)	1080i (Multi Screen: 720p)
Input	Video	1x VGA (D-Sub) | 1x DVI	1x VGA (D-Sub) | 2x HDMI | 1x Composite (BNC) | 1x Component (BNC) | 1x S-Video				
	Audio	Audio Jack	1x PC Audio | 1x Component Audio | 1x Composite Audio				
Output	Video	n/a	1x VGA (D-Sub) | 1x DVI (HDMI connector) | 1x Composite (BNC) | 1x Component (BNC)				
	Audio	n/a	Speaker (ready)				
	Data	1x RS232C					
Control	Multi-Screen Function	n/a	HDMI, D-Sub, Component, Composite				
	OSD Language	GB / DE / FR / ES / IT / PT / SE / DK / FI					
Power	Input Voltage	100~240VAC	100~240VAC	100~240VAC	100~240VAC	100~240VAC	100~240VAC
	Power consumption	50 W	140 W	200 W	200 W	220 W	260W
Options	Tempered Glass (Option)	D220MLG	D320MLG	D405MLG	D407MLG	D425MLG	D466MLG
	Touch Screen (Option)	D220MLI	D320MLI	D405MLI	D407MLI	D425MLI	D466MLI
	Other features	n/a	Auto Cooling System (1EA), Auto Power Control (On/Off Timer), Edge Correction				
Dimension	Wall Mounting (WxH) (mm)	100 x 100	400 x 200	400 x 200	400 x 200	600 x 200	600 x 200
	W x H x D (mm)	518.7 x 310.1 x 58.4	764 x 454 x 114.3	955.4 x 554.4 x 117.1	915 x 527.5 x 123.6	987.4 x 580.4 x 120.4	1051.2 x 604.4 x 128.3
	Bezel Size (U/D/L/R) (mm)	20/20/20/20	30/30/32/32	26.7/ 26.7/ 33.5/ 33.5	13.3/ 13.3/ 13.3/ 13.3	27.2/ 27.2/ 27.2/ 27.2	14.4/ 14.4/ 14.9/ 14.9
Weight	Set (kg)	8,4	19	31	28	32	33,5
Accessories		Manual, VGA Cable, DVI Cable	Power Cord, Manual, HDMI Cable, Remote Control				

Metal Frame Displays

Model		D465ML	D467ML	D468FL	D525ML	D705MLG	D825MLG
				NEW			
Panel	Screen Size (diagonal)	116,8 cm | 46"	116,8 cm | 46"	116,8 cm | 46"	132,1 cm | 52"	177,8 cm | 70"	208,3 cm | 80"
	Panel Type	S-PVA	S-PVA	S-PVA	S-PVA	S-PVA	S-PVA
	Active Display Area (mm)	1018.08 x 572.67	1018.08 x 572.67	1018.35 x 572.54	1152 x 648	1549.44 x 871.56	1805.76 x 1015.74
	Resolution	1920 x 1080	1920 x 1080	1366 x 768	1920 x 1080	1920 x 1080	1920 x 1080
	Aspect Ratio	16:9	16:9	16:9	16:9	16:9	16:9
	Display Colors	16.7 M	16.7 M	16.7 M	16.7 M	16.7 M	16.7 M
	Brightness (Typ)	450 cd/m²	700 cd/m²	700 cd/m²	600 cd/m²	600 cd/m²	600 cd/m²
	Contrast Ratio	4000:1	4000:1	3000:1	1700:1	2000:1	1200:1
	Response Time	8 ms	8 ms	8 ms	8 ms	8 ms	8 ms
	Viewing Angle	178°/178°	178°/178°	178°/178°	178°/178°	178°/178°	178°/178°
	Lifetime	50,000h	50,000h	50,000h	50,000h	50,000h	50,000h
Resolution	Monitor (Frequency H/V)	1920 x 1080 (67,5kHz/60Hz)	1920 x 1080 (67,5kHz/60Hz)	1360 x 768 (49,02kHz/60Hz)	1920 x 1080 (67,5kHz/60Hz)	1920 x 1080 (67,5kHz/60Hz)	1920 x 1080 (67,5kHz/60Hz)
	DTV	1080p (Multi Screen: 1080p)	1080p (Multi Screen: 1080p)	1080i (Multi Screen: 720p)	1080p (Multi Screen: 1080p)	1080p (Multi Screen: 1080p)	1080p (Multi Screen: 1080p)
Input	Video	1x VGA (D-Sub) | 2x HDMI | 1x Composite (BNC) | 1x Component (BNC) | 1x S-Video					
	Audio	1x PC Audio | 1x Component Audio | 1x Composite Audio					
Output	Video	1x VGA (D-Sub) | 1x DVI (HDMI connector) | 1x Composite (BNC) | 1x Component (BNC)					
	Audio	Speaker (ready)					
	Data	1x RS232C					
Control	Multi-Screen Function	HDMI, D-Sub, Component, Composite					
	OSD Language	GB / DE / FR / ES / IT / PT / SE / DK / FI					
Power	Input Voltage	100~240VAC					
	Power consumption	260 W	260 W	260 W	320 W	900 W	900 W
Options	Tempered Glass (Option)	D465MLG	D467MLG	n/a	D525MLG	yes	yes
	Touch Screen (Option)	D465MLI	D467MLI	n/a	D520MLI	D705MLI	n/a
	Other features	Auto Cooling System (1EA), Auto Power Control (On/Off Timer), Edge Correction					
Dimension	Wall Mounting (WxH) (mm)	600 x 200				600 x 400 | 600 x 400	600 x 600
	W x H x D (mm)	1087.4 x 631.4 x 114.5	1051.2 x 604.4 x 129.3	Open Frame	1196.4 x 692.4 x 127.9	1919.8 x 1088.0 x 158.3	1883 x 1088 x 164.5
	Bezel Size (U/D/L/R)	28 / 28 / 33.3 / 33.3	14.4 / 14.4 / 14.9 / 14.9	Open Frame	20.2 / 20.2 / 20.2 / 20.2	34.1 / 34.1 / 36.6 / 36.6	36.6/36.6/34/34
Weight	Set (kg)	38,5	32	26	46.2	95	135
Accessories		Power Cord, Manual, HDMI Cable, Remote Control					

Touch Screen Displays

Model Name	D190MLI	D320MLI	D40(5/7)MLI	D425MLI	D46(5/7)MLI	D525MLI	D705MLI
	NEW						
General Specification	see datasheet	Please refer to the specification of the corresponding models of standard metal frame displays.					
Touch Size (W x H x D) (mm)	518.4 x 324.0	809 x 482 x 11.5	968 x 573 x 14.5	1023 x 615 x 14.5	1105 x 653 x 14.5	1242 x 742 x 14.5	1692 x 1014 x 10
Resolution	1440 x 900	8384 x 4736	10624 x 6016	10432 x 5824	11456 x 6400	12928 x 7296	16384 x 9856
Response Time (ms)	Touch: 16 Drawing: 25	Touch: 16 Drawing: 25	Touch: 21 Drawing: 33	Touch: 8 Drawing: 13	Touch: 10 Drawing: 15.2	Touch: 14 Drawing: 21	Touch : 11 Drawing : 16
Glass	Option	Transmission: 92% up to 100%, Thickness: 5mm with anti-vandal					
Available object size for Touch (mm)	Touch: ø7 Stylus: ø8	Touch: ø5 Stylus: ø6	Touch: ø6 Stylus: ø7	Touch: ø7 Stylus: ø8	Touch: ø6 Stylus: ø7	Touch: ø6 Stylus: ø7	Touch: ø7 Stylus: ø8
Interface	USB 2.0						
Weight (kg)	7	5,5	8,5	12	12	14	14
Power (W)	25	7,5	7,5	7,5	7,5	7,5	7,5
Touch Intensity	Over 60,000,000						
Detection Method	Capacitive	Infrared Rays					

Technical details are subject of changes without further notice. Errors expected.

Accessories

Table Stand Type A – landscape (Option)



Table Stand Type B – portrait/landscape (Option)



Indoor Digital Signage | Technical Specification

Optical Bonding & Transflective Displays

Model		D407MLP (NEW)	D466MLP (NEW)	D407MLT	D466MLT (NEW)	D467MLT
Panel	Typ	Optical Bonding	Optical Bonding	Transflective	Transflective	Transflective
	Screen Size	101,6 cm | 40"	116,8 cm | 46"	101,6 cm | 40"	116,8 cm | 46"	116,8 cm | 46"
	Active Display Area (mm)	885.6 x 498.15	1018.35 x 572.54	885.17 x 497.66	1018.35 x 572.54	1018.35 x 572.54
	Resolution	1920 x 1080	1366 x 768	1920 x 1080	1366 x 768	1920 x 1080
	Aspect Ratio	16:9	16:9	16:9	16:9	16:9
	Display Colors	16.7 M	16.7 M	16.7 M	16.7 M	16.7 M
	Brightness (Typ)	700 cd/m²	1500 cd/m²	700 cd/m²	1500 cd/m²	700 cd/m²
	Brightness max. (at 80K lux conditions)	—	—	960 cd/m²	2400 cd/m²	1500 cd/m²
	Contrast Ratio	3000:1	3000:1	2000:1	3000:1	2000:1
	Response Time	8 ms	8 ms	9 ms	8 ms	8 ms
	Viewing Angle	178°/178°	178°/178°	178°/178°	178°/178°	178°/178°
	Lifetime	50,000h	50,000h	50,000h	50,000h	50,000h
Resolution	Monitor (Frequency H/V)	1920 x 1080 (67,5kHz/60Hz)	1360 x 768 (49,02k Hz/60Hz)	1920 x 1080 (67,5kHz/60Hz)	1360 x 768 (49,02k Hz/60Hz)	1920 x 1080 (67,5kHz/60Hz)
	DTV	1080p (Multi Screen: 1080p)	1080i (Multi Screen: 720p)	1080p (Multi Screen: 1080p)	1080i (Multi Screen: 720p)	1080p (Multi Screen: 720p)
Optical Bonding	Light Transmittance	98%	98%	—	—	—
	Light Reflectance	1%	1%	—	—	—
Input	Video	1x VGA (D-Sub) | 2x HDMI | 1x Composite (BNC) | 1x Component (BNC) | 1x S-Video				
	Audio	1x PC Audio | 1x Component Audio | 1x Composite Audio				
Output	Video	1x VGA (D-Sub) | 1x DVI (HDMI connector) | 1x Composite (BNC) | 1x Component (BNC)				
	Audio	Speaker (ready)				
	Data	1x RS232C				
Control	Multi-Screen Function	HDMI, D-Sub, Component, Composite				
	OSD Language	GB / DE / FR / ES / IT / PT / SE / DK / FI				
	Auto Power Contr. (DPMS)	yes				
Power	Input Voltage	100~240VAC	100~240VAC	100~240VAC	100~240VAC	100~240VAC
	Power consumption	220 W	260 W	200 W	320 W	260 W
Options	Tempered Glass (Option)	D407MLPG	D466MLPG	D407MLTG	D466MLTG	D467MLTG
	Touch Screen (Option)	D407MLPI	D466MLPI	D407MLTI	D466MLTI	D467MLTI
	Other features	Auto Cooling System (1EA), Auto Power Control (On/Off Timer), Edge Correction				
Dimension	Wall Mounting (WxH) (mm)	400 x 200	600 x 200	400 x 200	600 x 200	600 x 200/400
	W x H x D (mm)	916 x 528.5 x 128.6	1051.2 x 604.4 x 132.8	916 x 528.5 x 128.6	1051.2 x 604.4 x 132.8	1051.2 x 604.4 x 132.8
	Bezel Size (U/D/L/R) (mm)	13.3 / 13.3 / 13.3 / 13.3	14.4 / 14.4 / 14.9 / 14.9	13.3 / 13.3 / 13.3 / 13.3	14.4 / 14.4 / 14.9 / 14.9	14.4 / 14.4 / 14.9 / 14.9
Weight	Set (kg)	31	39	28	33.5	39
Evironment Conditions	Temperature (°C)	0 - 40				
	Humidity (%)	20 -80				
Accessories		Power Cord, Manual, HDMI Cable, Remote Control				

Technical details are subject of changes without further notice. Errors expected.

Warranty Terms

HYUNDAI IT display products are high advanced technology products. By following international development and production standards, we always ensure the best product quality and thus high product reliability. Nevertheless, in case of any service event, we provide a fast and credible after-sales support. According to the customer needs we are providing different service levels.

SERVICE LEVEL	DESCRIBTION
STANDARD	2 years pick-up, repair & return
HOME-IN	On-Site analysis by engineer. If necessary a defective unit will be immediately replaced. Customer is free in un-installation and delivery time consumption.
PREMIUM	Wherever product is displayed, in next business day it is reworking. Warranty extension up to 5 years. Includes configuration, delivery, installation and maintenance.

All-in-One Displays

Model		P425MN (NEW)	P467MN (NEW)
Panel	Screen Size	106,7 cm | 42"	116,8 cm | 46"
	Active Display Area (mm)	930.3 x 523.0	1018.08 x 572.67
	Resolution	1920 x 1080 (WUXGA)	1920 x 1080 (WUXGA)
	Aspect Ratio	16:9	16:9
	Display Colors	16.7 M	16.7 M
	Brightness (Typ)	500 cd/m²	700 cd/m²
	Contrast Ratio	1000:1	4000:1
	Response Time	8 ms	8 ms
	Viewing Angle	178°/178°	178°/178°
	Lifetime	50,000h	50,000h
Resolution	Monitor (Frequency H/V)	1920 x 1080 (67,5kHz/60Hz)	1920 x 1080 (67,5kHz/60Hz)
	DTV	1080p (Multi Screen: 1080p)	1080p (Multi Screen: 1080p)
Input	VGA (D-Sub)	1	1
	LAN	1	1
	USB	3	3
	RS232C	1	1
Output	Speaker	1	1
Power	Input Voltage	100~240VAC	100~240VAC
	Power consumption/ DPMS	320 W/2W	360 W/2W
Others	Auto Cooling System	yes (1EA)	yes (1EA)
	Tempered Glass	Option	Option
	Touch Screeen	Option	Option
	Player Type	PC	PC
	Other features	Auto Power Control (On/Off Timer), Edge Correction	Auto Power Control (On/Off Timer), Edge Correction
Dimension	Mounting Hole	600 x 200	600 x 200
	W x H x D (mm)	987.4 x 580.4 x 120.4	1051.2 x 604.4 x 128.3
Weight	Set (Kg)	32	36.5

Built-in PC | Specification	
CPU	CPU Intel Celeron Upto Core2Duo
	FSB 533/800/1066 Supported
Graphic	Intel 945G GMCH & 82801GB(R)
Memory	DDR2 SDRAM 1GB up to 3GB
HDD	2.5" SATA 80GB
LAN	Ethernet 100/1000 base
RS232	1
USB V2.0	3
Keyboard	1
Mouse	1

Wide View Displays

Model Name			C420MK
Display Panel		Screen Size	97 cm | 38,2"
		Active Display Area (mm)	930.25 x 272.40
		Number of Pixels	1366 x 400
		Aspect Ratio	3.4 : 1
		Display Colors	16.7 Mil.
		Brightness (cd/m²) / (typ)	500
		Contrast Ratio	800 : 1
		Response Time (ms, GTG)	9
		Viewing Angle (H°/V°)	178° / 178°
		Life Time	50,000h
Resolution		Monitor	1360 x 768
		DTV	1080i
Connectivity & Control"	Input	VGA (15pin D-Sub)	1
		HDMI	1
		DVI	1
		Component (RCA)	1
		PC Audio	1
		Component Audio	1
		RS232C	1
	Output	Speaker (Ready)	1
	Power Requirement	Input Voltage	100 – 240VAC
		Consumption (typ) (W)	50
	Auto Power Control (DPMS)		Yes
Feature	Tempered Glass		Option
Mechanical	Dimension (mm)	Set (W x H x L) (mm)	987.5 x 332 x 113.5
	Weight (kg)	Set Weight (kg)	22,5
	Accessories		Power cord, Manual, D-Sub Cable, Remocon
Approvals	EMI/EMC		FCC, CE
	Safety		cTUVus, TUV, CB
Temperature			0°C – 40°C
Humidity			20% – 80%
Wall Mounting Hole (W X H mm)			600 x 200

HYUNDAI

UV Ray Sterilization

Most micro-organisms get into the human body through the air and the dust on the skin. Ultraviolet germicidal irradiation (UVGI) is one of the most efficient sterilizing solutions due to UV-C ray's capability (intensity: approx. 12K µW/cm2) to kill more than 90% of known micro-organisms. The application of UVGI has been used primarily in medical sanitation and expands nowadays for various purposes, like water or air purification. The ADCALTOR ™ is equipped with an UV sterilization system in order to keep the handrails of escalators or moving walkways clean.



Accident Precaution

Most accidents on escalators or moving walkways happen to children under 12 years or elderly persons being older than 55 years. In most cases carelessness is the main reason for accidents. In order to prevent or minimize such kind of accidents, the ADCALATOR™ offers an effective solution to draw the passenger's attention by displaying security advises on the screens.



Master/Slave Configuration

The ADCALATOR™ is always installed in pairs - there is a master and a slave. The master device contains the multimedia player. The slave is connected to the master for video (HDMI), audio and remote control (RS232). Each device contains one speaker for the stereo audio system.

Remote Administration

The ADCALATOR™ offers the possibility of remote control for administration services. Once being connected to network/internet it allows the following control functions:

- Content upload & download
- Content scheduler
- Firmware upgrade
- System power on/off
- UV sterilization system: on/off, scheduler
- Collection of system log data
- Monitoring of player

Why ADCALATOR™?

- Growth for advertising expenditure only expected for OOH media until 2011.
- Climate change abets widespread of vector-borne diseases.
- 50% of world populaton lives already in urban areas. 70% will live in cities by 2050.
- More than 85 K escalators and moving walk already installed in the EU and there are minimum 85K new installations every year.

Main Specifications	
Processor (CPU)	Sigma Design EM8621 (1080p support) (Intel CPU from Q1/2010)
Operating System	Linux embedded
Display	50,8 cm/20" diagonal, 16:9, PVA panel with LED backlight
Memory	Flash 16MB, SDRAM 64MB
Storage	CF/USB/2,5"HDD
Audio	stereo speakers
Remote Control	RS232C
Display	50,8 cm/20" diagonal, 16:9, PVA panel with LED backlight
Surface	anti-vandal glass, anti-reflection coating

Technical details are subject of changes without further notice. Errors expected.

ADCALATOR™ NEW

The ADCALATOR™ is a digital signage solution that also cares for health and safety related needs. Being installed at the entrance of escalators or moving walkways it offers digital signage operations on a highly frequented installation side. The integrated multimedia player (supporting even HD contents), a content management application and the possibility of remote control make the ADCALATOR™ a flexible digital signage solution. Due to a smart mounting system and the capability of being connected to a wireless LAN it can be easily installed to existing escalators and moving walkways.

Indoor Digital Signage | Stand-Alone

Versatile Single Screen Information Signage

The HYUNDAI IT Stand-Alone Public Displays are the best solution for single screen information signage. Combining dynamic screen contents and the static depiction of your corporate identity the Stand-Alone Public Displays bring the maximum brand communication to the Point of Information. Exhibitions, hotel and office lobbies, customer waiting areas and retail shops are some examples for the versatile fields of operation.

Like all HYUNDAI IT Public Display products the Stand-Alone Type is equipped with an Out-Of-Home LCD Panel which brings the advantages of 24/7 operation, a high contrast and brightness as well as the opportunity of using the panel in portrait or landscape format.

Flexible Content Management

Providing sufficient space in the cabinet and coping with a variety of video connectors the HYUNDAI IT Stand-Alone Displays can be equipped with a PC or any other AV player. In combination with digital signage software and the opportunity to update the contents via LAN, WLAN or 3G the Stand-Alone Displays are the easiest and most cost effective way to deliver your messages to your target audience.

Full Protection

In order to protect the high-tech components and ensure a long life the housing is fully made of steel and can be locked. The panel is protected by a special tempered glass which supports a clear image of the screen contents.

Touch Screen Function (Option)

Optionally, the Stand-Alone Displays are available as touch screen models. The used infrared touch screen technology ensures maximum controlling comfort and makes them ready for a lot of interactive applications.

Easy Individualization



Class			D467SL	D525SL
Panel		Screen Size	116,8 cm | 46"	132,1 cm | 52"
		Active Display Area	1018.4 x 572.5	1152 x 648
		Number of Pixels	1920 x 1080 (WUXGA)	
		Aspect Ratio	16:9	16:9
		Display Colors	16.7 Mil	16.7 Mil
		Brightness	700 cd/m^2	600 cd/m^2
		Contrast Ratio	4000:1	1700:1
		Response Time (ms)	8	8
		View Angle (H/V)	178° / 178°	178° / 178°
		Life Time	50,000h	50,000h
Resolution (Max)		Monitor	1920 x 1080	1920 x 1080
		DTV	1080p	1080p
Connectivity & Control	Input	VGA (D-Sub)	1	1
		HDMI	1	1
		Composite (BNC)	1	1
		Component (BNC)	1	1
		PC Audio	1	1
		RS232C	1	1
		Component Audio	1	1
		Composite Audio	1	1
	Output	VGA (15pin D-Sub)	1	1
		HDMI	1	1
		Composite (BNC)	1	1
		Component (BNC)	1	1
		Audio	1	1
		RS232C	1	1
		Speaker (Ready)	15W x 2CH	15W x 2CH
Feature		Tempered Glass	Yes	Yes
		Auto Cooling System	Yes	Yes
		Touch Screen	Option: D467SLI	Option: D525SLI
Auto Power Control			Yes	Yes
OSD Language			10 Language	10 Language
Dimension		Set (WxHxL) (mm)	701.8 x 1992 x 500	780.4 x 1900 x 500
		Stand Included (WxHxL) (mm)	696 x 1892 x 500	780.4 x 2000 x 500
Set Weight (kg)			120	135
Accessories			Power cord, Manual, HDMI Cable, Remote Control	

Technical details are subject of changes without further notice. Errors expected.

HYUNDAI

Stereoscopic 3D Displays

A New Dimension in Display Technology

In addition to conventional 2D operations HYUNDAI IT's stereoscopic 3D displays make it possible to watch 3D images with a breathtaking three-dimensional effect. For example 3D models created with CAD software can be displayed more plastically and thus allow a presentation close to reality. Beside professional applications the 3D displays are also suitable for multimedia operation such as 3D games, movies or pictures.

Based on the stereoscopic 3D technology the viewer watches the 3D contents on a polarized 3D display by wearing polarized 3D glasses. A stereoscopic image combines two images that represent the views of the left and the right eye with different perspective view points.. From these two slightly different views, the eye-brain synthesizes an image of the world with stereoscopic depth.



Side by Side format image.

Recognition of left eye's image.

Recognition of right eye's image.

Polarized glasses

Key Features

- Moire, ghosting and flicker free
- High contrast ratio and fast response time
- HDMI with HDCP support
- Wide viewing angle
- Certified for Windows Vista

3D Visualizer/OpenGL driver (Option)

3D Visualizer enables selected third party applications to work on HYUNDAI IT's 3D displays. Using 3D displays and 3D Visualizer, 3D models appear to have a real physical depth, just like the actual objects they are modelling.

For more information on DDD's TriDef software please visite: http://www.tridef.com.

3D Software Package

HYUNDAI IT's 3D display comes along with a software package of the leading 3D software supplier DDD:

- 3D Media Player
- 3D Experience
- 3D Google Earth
- 3D games driver

DDD TriDef 3-D Experience

Recommended Hardware Requirements

Intel® Core 2 Duo or Athlon™ 64 X2 Dual-Core CPU, 1GB RAM, NVIDIA® GeForce 6600 or ATI Radeon™ X800, 100MB free disk space, Windows® XP, Vista (32Bit), DirectX 9.0c compatible sound card, Internet connection, DVD-ROM drive, Network card.

Model Name		W220S	W240S	S320D	S465D
3D Technology	Filter	Circular polarized filter			
	Compatibility | Conversion	2D/3D compatibel | 2D/3D Conversion			
	3D Format	Horizontal interlaced			
	Viewing Angle (H/V)	160°/10°	160°/10°	178°/20° (typ. CR:10)	178°/20° (typ. CR:10)
	Supported 3d Resolution	1680 x 1050	1920 x 1200	1366 x 768	1920 x 1080
	Viewing Distance (Recom.)	70 cm	70 cm	Over 1.5 m	Over 1.5 m
Panel	Type	A-Si TFT Active Matrix	A-Si TFT Active Matrix	A-Si TFT Active Matrix	A-Si TFT Active Matrix
	Size (diagonal) Display Area (H/V)	55.9 cm (22") 473.7 x 296.1 mm	61 cm (24") 518.4 x 324 mm	81.3 cm (32") 697.7 x 392.3 mm	116.8 cm (32") 1018.4 x 572.5 mm
	Pixel Pitch (H/V)	0.282 x 0.282 mm	0.270 x 0.270 mm	0,51075 x 0,51075 mm	0.530 x 0.530 mm
	Viewing Angle (H/V)	160° / 160° (CR:<=10)	178° / 178° (CR:<=10)	178° / 178° (CR:<=10)	178° / 178° (CR:<=10)
	Contrast Ratio	1,000:1 / 10,000:1 (DCR)	1,000:1 / 10,000:1 (DCR)	3,000:1 / 6,000:1 (DCR)	3,000:1 / 6,000:1 (DCR)
	Response Time	5 ms (typical)	6 ms (typical)	8 ms (GtG)	8 ms (GtG)
	Brightness	300 cd/m² (typical)	500 cd/m² (typical)	500 cd/m² (typical)	500 cd/m² (typical)
	Aspect Ratio	16:10	16:10	16:9	16:9
	Colors	16.7 M	16.7 M	16.7 M	16.7 M
Resolution	Maximum / Recommended	1680 x 1050 @ 60Hz	1920 x 1200 @ 60Hz	1360 x 768 @60Hz	1920 x 1080 @ 60Hz
	Video	480p, 576p, 720p, 1080i/p	480p, 576p, 720p, 1080i/p	480p, 576p, 720p	480i/p, 576i/p, 720p, 1080i/p
Input Signal	Analog RGB / DVI-D	1/1	1/1	1/-	1/-
	HDMI-HDCP / Component	1/-	1/1	1/1	1/1
	S-Video/Composite	-/-	-/-	1/1	1/1
	PC Audio	Yes	Yes	Yes	Yes
Plug-and-Play		VESA DDC 2B	VESA DDC 2B	VESA DDC 1/2B	VESA DDC 1/2B
Power Management		VESA DPMS	VESA DPMS	VESA DPMS	VESA DPMS
Power	Voltage	100-240V AC 2.0A	100-240V AC 2.0A	100-240V AC 5.0A	100-240V AC 5.0A
	Consumption	45 Watt (typical)	85 Watt (typical)	150 Watt (typical)	230 Watt (typical)
	Type	Internal Power Supply	Internal Power Supply	Internal Power Supply	Internal Power Supply
Safety & Regulations		cTUVus, CB, EK, PSE, FCC, CE, VCCI, Energy Star		cTUVus, CB, FCC, CE	
Other Features	Audio System	Internal Loudspeaker 2 x 3 Watt, PC Audio In/Out		max. 10W x 2ch	
	Kensington Slot / Wallmount Holes	Yes | Yes (VESA: 100 x 100 mm)		Yes | Yes (200 x 100 mm)	Yes | Yes (580 x 420 mm)
Stand	Type	Tiltable	Tilt /PIVOT/height-adj.	Tiltable	Tiltable
Cabinet Color		Black/White high gloss design	Black/White high gloss design	Black	Black
Dimensions	Unit (W x H x D)	522 x 412 x 210 mm	522 x 412 x 210 mm	806x617x229 mm	1143 x 310 x 845 |
Weight	Unit (kg)	7.3	10	17	30
Scope of Accessories		Power cable, DVI Cable, D-Sub Cable, Audio Cable, Quick Installation guide, 3D glasses, HDMI-DVI Cable(S465D only) CD-ROM: User manual, Driver, ICM profil, 3D software package			

Technical details are subject of changes without further notice. Errors expected.

HYUNDAI

Touch Screen Displays

Get in Touch with a New Interface

The HYUNDAI IT LCD touch screen monitors unite the newest touch screen technology and timeless design with an optimal price-performance ratio. They can be used for POS or monitoring & control applications.

Key Features

- reliable functionality thanks to 5-wire resistive touch screen technology
- robust design by hard surface (3H) and well fixing dual hinge stand
- sharp and brilliant pictures by high contrast and brightness

		G70TR	G90TR
Touch Screen Technology	type	5-Wire Resistive Touch Screen	5-Wire Resistive Touch Screen
	controller interface	USB	USB
	surface type | hardness	anti-glare | 3H	anti-glare | 3H
	light transmission	>81%	>81%
	response time: touch / drawing	< 10 ms (typical) / 35 ms (max.)	< 10 ms (typical) / 35 ms (max.)
	touch accuracy	98.5~99%	98.5~99%
	environment	indoor/outdoor, moisture and dust resistant	indoor/outdoor, moisture and dust resistant
	operating temperature	0°C ~ +50°C	0°C ~ +50°C
	lifetime	tested to perform over 30 million touches on a single point	
	resolution	2048 x 2048	2048 x 2048
	input mode	bare or gloved finger, stylus, pen etc.	bare or gloved finger, stylus, pen etc.
	function	senses pressure exerted on the screen	senses pressure exerted on the screen
Panel Technology	LCD	A-Si TFT Active Matrix / TN	A-Si TFT Active Matrix / TN
Panel Specifications	size: diagonale | active display area	17" (43,18 cm) | 337.9 x 270.3 mm	19" (48,26 cm) | 376.3 x 301.1 mm
	viewing Angle	160° / 160° (horizontal / vertical)	160° / 160° (horizontal / vertical)
	pixel pitch	0,264 mm (H x V)	0,264 mm (H x V)
	contrast ratio	800:1 (typical)	1000:1 (typical)
	luminance	300 cd/m2 (typical)	300 cd/m2 (typical)
	response time	Tr=1.5ms, Tf=3.5ms (typical)	Tr=1.5ms, Tf=3.5ms (typical)
	aspect ratio	5:4	5:4
	colors	16,7 M	16,7 M
Resolution	maximal | recommended	1280 x 1024 @ 75 Hz | 1280 x 1024 @ 60 Hz	1280 x 1024 @ 75 Hz | 1280 x 1024 @ 60 Hz
Connectors	analog | digital	15-pin D-Sub | 24-pin DVI-D	15-pin D-Sub | 24-pin DVI-D
Plug-and-Play		VESA DDC 1/2B (EDID 1.3)	VESA DDC 1/2B (EDID 1.3)
Power Management		VESA DPMS	VESA DPMS
Power Supply System	voltage | consumption | type	100 – 240V AC 1.5A | 32 Watt | external DC 12V	100 – 240V AC 1.5A | 36 Watt | external DC 12V
Safety & Regulations		NRTL, CB, TUV-GS, FCC, CE, RoHS, WEEE, ISO 13406-2 (class 2)	
Other Features	audio system	2 W x 2ch/earphone jack	2 W x 2ch/earphone jack
	Kensington slot | Wallmounting holes	yes | yes (VESA: 75 x 75mm)	yes | yes (VESA: 75 x 75mm)
Stand	type	dual hinge stand, heigt-adjustable	dual hinge stand, heigt-adjustable
Cabinet Color		black	black
Dimensions	unit | packed (W x H x D)	382 x 403 x 200 mm | 436 x 378 x 140 mm	420 x 405 x 170 mm | 483 x 415 x 212 mm
Weight	unit | packed	4.95 kg | 6.4 kg	5.8 kg | 7.7 kg
Scope of Delivery		Power cord, D-Sub cable, audio cable, USB cable, warranty card; CD-ROM: user manual, monitor driver, touch screen driver	

Technical details are subject of changes without further notice. Errors expected.

The HYUNDAI IT Story

HYUNDAI Electronics first set up a monitor division at its electronics corporation in 1984. After launching the first monochrome monitor, HYUNDAI continuously developed its product range, rapidly succeeding in expanding production to over 1 million units per year. HYUNDAI has been a leading manufacturer of TFT displays in a variety of sizes since the mid-1990s. In 2000, the monitor division parted company with the parent corporation to become what is today Hyundai IT Corp. Ltd., Korea, and associated HYUNDAI IT Europe GmbH. The company operates in-house research, development and production facilities to guarantee cutting-edge technology at all times and maximize customer satisfaction. "We focus on providing flawless, comprehensive service and after-sales support. We will continue to focus operations according to the needs of our customers, and combine state-of-the-art technology with the highest service standards", states President of HYUNDAI IT Europe GmbH, Mr. Y.H. Shin, in confirmation of the company's recipe for success.

Full Product Portfolio

Being an expert for digital display solutions, HYUNDAI IT is offering a full range of products for both consumer as well as professional customers:

LCD Monitor

Monitor + TV

3D Monitor

Touch Screen Monitor

HYUNDAI

3D Display

Indoor Digital Signage

Indoor Stand-Alone

Outdoor Digital Signage

HYUNDAI

Digital Signage | Selection of References

Customer/Location:
Sky72 CC
Incheon, South Korea
Products:
46" Outdoor
2x2 Multi Screen
Installation:
August 2009



Customer/Location:
Lanarka Airport
New Terminal, Cyprus
Products:
40"/46" Multi-Screen
52" Stand-Alone
Installation:
November 2009



Customer:
Shopping Mall
Seoul, Korea
Products:
46" Multi-Screen
(1x33)
Installation:
August 2008



Customer/Location:
Shopping Mall
Trondheim, Norway
Products:
9x 40" D400ML
3x3 Multi Screen
Installation:
November 2009



Customer/Location:
Airport (1F Entrance)
Kimpo, Korea
Products:
40" Multi-Screen
(3x16)
Installation:
February 2009



Customer/Location:
Multiplex Cinema
(Myeong-dong, Seoul,
South Korea)
Products:
46" Multi-Screen (3x3)
Installation:
May 2009

Customer/Location:
Shopping Mall
Tornio, Finland
Products:
9x D460ML
3x3 Video Wall
Installation:
August 2009



Customer/Location:
Barcelona Airport,
Terminal 1, Spain
Products:
22x 70" Single-Screen
& Totem
Installation:
November 2009

Customer/Location:
Bus Shelter
Seoul, Korea
Products:
4 locations
46" Outdoor (LED)
Installation:
December 2009



Customer/Location:
63 Building
Seoul, Korea
Products:
46" Multi-Screen
(3x3)
Installation:
June 2009



Customer/Location:
Päivälehtimuseo
Museum, Finland
Products:
D320MLI
5x Touchscreen
Installation:
Dezember 2009



Customer/Location:
Citroen dealer shops
France, Italy, UK
Products:
40" Metal Frame
19" Touch Screen
Installation:
Start: January 2010

HYUNDAI